



SWINGULATOR SWEEP TRAINER 1- XT PRODUCT INFORMATION SHEET

Single-Seat Team Trainer with Water Table

FOOTPRINT	WIDTH (ft)	LENGTH (ft)	WIDTH (m)	LENGTH (m)
1 Unit (1 seat)	6.0	7.7	1.8	2.3
1 Unit (2 seats)	10.0	12.4	3.3	4.1
WEIGHT: 1 UNIT (2 seats)			lb	kg
Shell with seats and foot stretchers			350	159
Oars with end caps (2)			16.2	7.4
Water Tables (2)			30	14
C2 Ergs w/o seat or I-beam (2)			78	35
Total Machine Weight			474.2	216
SHELL / RIGGER			in	cm
Deck width - at base			18	45.6
Deck width - inside edge to gunwale			20.8	52.7
Deck depth			5.5	14
Spread (center of boat to center of pin)			32.7 +/- 1.2	83-87 (set at 84)
Inboard (outboard side of collar to tip of handle)			45.3 +/- 1.2	115 +/- 3 (set at 115)
Outboard Travel (center of pin to center of wheel)			23.4 +/- 1.2	59.5 +/- 3 (set at 59.5)
OAR / TABLE			lb	kg
Concept 2 Carbon Fiber Oar - Medium Stiffness				
Oar Weight (fully assembled)			8.1	3.7
Oar Shaft Angle (oar lock at medium setting)			degrees	degrees
- On Drive			8-9	8-9
- On Recovery			5-6	5-6
Oar Length - tip of handle to center of wheel (with handle in shortest length setting)			in	cm
			69.5	176.5
Oar Handle Length Adjustment			2.0	5.0
Collar Location - from tip to handle			115 cm - outside edge of inside collar 122 cm - outside edge of outside collar	
Oar Lock vertical adjustment range			1.25	3.2
Handle height range			6	15.2
Table Height to top surface			27.2	69
SEAT ASSEMBLY			in	cm
Fiberglass Racing Seat with Aluminum tracks				
Wheel Spread - on center			11.8	30
Height range in carriage (3 settings - machine set at middle)			0.5	1.3
Travel			35.4	90
FOOTSTRETCHER			in	cm
Steel foot board with C2 Flexfoot				
Track adjustability Range			9.8	24.8

Rev.18